



Sheets 1200 x 800 mm	VE 5 Sheets box (4,8 m ²) or on Pallet
Sheets 800 x 400 mm	VE 5 sheets box (1,6 m ²) or on Palett
Sheets 1900 x 800 mm	Flat lying on palett to inquiry
Sealing Base coat and top coat	XSTONE HARDTPROTECT
Recycling	Household waste
Bonding	Self-adhesive
Processing video	www.xstonedesign.com

Total thickness of the plate	4 mm
Width and length in mm	1180 x 780 oder 400 x 800 or 1900 x 800
Fire class on mineral reason	Bfl - s1
Test method	EN ISO 9239-1:2010
Weight per m ²	ca. 3,9 kg pro m ²
Swelling behavior EN 13329, APX G	< 0,2 %
Slip resistance	R 10
Shock load	IC 2, Nachbearbeitung mit XSTONE Kit
Impact sound insulation	- 21 dB
Color fastness	gegeben
Chemical compatibility	gegeben

Packaging, storage, recycling, gluing and sealing

Responsibility	Our product base is FREE OF Plasticizers, asbestos, Formaldehyde, halogens as well Heavy metals and meets the VOC Guideline afsset A +, sheet angel and des AGBB schemes
Ecology	It is neither solvent, nor other ozone-depleting Contain substances. The one for that Product used, renewable raw materials not in competition with Food growing.
Osh	The product does not require special Occupational health and safety measures. Note our laying Manual
Product structure	Permanently elastic material consisting of mineral Fillers and polyurethane Binders



+44 7539 855216



info@xstonedesign.com



Units A1&A2 Stirling Road
South Marston Ind Estate
Swindon SN34TQ
United Kingdom

All colors and textures	https://xstonedesign.com
Sample Request	info@xstonedesign.com